

**DAT 24" X 24" ECO GREEN ENVIRONMENT FRIENDLY NYLON CARPET:  
SPECIFICATIONS:**

Minimum Sq. Yd.	No minimum
Construction	Tufted
Surface Texture	Level Patterned Loop
Gauge	1/12 (49.00 rows per 10 cm)
Density	6120
Weight Density	104,040
Sustainable Content	Contains a minimum 35% pre-consumer recycled content by total weight
Stitches Per Inch	9.3 (36.61 per 10 cm)
Finished Pile Thickness	.100" (2.54 mm)
Dye Method	Solution Dyed
Backing Material	EcoFlex ICT
Fiber Type	Colorstrand® SD Nylon
Face Weight	17.0 oz. per sq. yd. (576 g/m2)
Pattern Repeat	Not Applicable
Size/Width	24" x 24" (.6096 m x .6096 m)
Soil Release Technology	Sentry Plus
Installation Method	Monolithic, Quarter Turn, Vertical Ashlar, Brick Ashlar, Multi-Directional
Indoor Air Quality	<a href="#">Green Label Plus 1098</a>
Foot Traffic Recommendation TARR	Heavy
NSF 140	Gold (Platinum option available)
PERFORMANCE	
Static	AATCC-134 Under 3.5 KV
Flammability	ASTM E 648 Class 1 (Glue Down)
Smoke Density	ASTM E 662 Less than 450
Others	<a href="#">Colorfastness to Light &amp; Atmospheric Contaminants</a> <a href="#">Stain Warranty</a>

"Color may vary from dye lot to dye lot. Substitution of material may be made due to improved technology, supply limitations, or other factors. The performance is not affected by such variances. All Specifications are subject to normal manufacturing tolerances."