

**SOLV 24" X 24" ECO GREEN ENVIRONMENT FRIENDLY NYLON CARPET:  
SPECIFICATIONS:**

Minimum Sq. Yd.	<b>No minimum</b>
Construction	<b>Tufted</b>
Surface Texture	<b>Textured Patterned Multi Colored Loop</b>
Gauge	<b>1/12 (49.00 rows per 10 cm)</b>
Density	<b>4800</b>
Weight Density	<b>96,000</b>
Stitches Per Inch	<b>12.0 (47.24 per 10 cm)</b>
Finished Pile Thickness	<b>.150" (3.81 mm)</b>
Dye Method	<b>Solution Dyed / Yarn Dyed</b>
Backing Material	<b>EcoFlex ICT</b>
Fiber Type	<b>Colorstrand® Nylon</b>
Face Weight	<b>20.0 oz. per sq. yd. (678 g/m<sup>2</sup>)</b>
Pattern Repeat	<b>Not Applicable</b>
Size/Width	<b>24" x 24" (.6096 m x .6096 m)</b>
Soil Release Technology	<b>Sentry Plus</b>
Installation Method	<b>Vertical Ashlar, Quarter Turn, Monolithic, Brick Ashlar</b>
Indoor Air Quality	<a href="#"><u>Green Label Plus 1098</u></a>
Foot Traffic Recommendation	<b>Severe</b>
TARR	
NSF 140	<b>Gold (Platinum option available)</b>
PERFORMANCE	
Static	<b>AATCC-134 Under 3.5 KV</b>
Flammability	<b>ASTM E 648 Class 1 (Glue Down)</b>
Smoke Density	<b>ASTM E 662 Less than 450</b>