

**VANI 24" X 24" ECO GREEN ENVIRONMENT FRIENDLY NYLON CARPET:
SPECIFICATION:**

Minimum Sq. Yd.	No minimum
Construction	Tufted
Surface Texture	Textured Patterned Multi Colored Loop
Gauge	1/12 (49.00 rows per 10 cm)
Density	4800
Weight Density	96,000
Stitches Per Inch	12.0 (47.24 per 10 cm)
Finished Pile Thickness	.150" (3.81 mm)
Dye Method	Solution Dyed / Yarn Dyed
Backing Material	EcoFlex ICT
Fiber Type	Colorstrand® Nylon
Face Weight	20.0 oz. per sq. yd. (678 g/m²)
Pattern Repeat	Not Applicable
Size/Width	24" x 24" (.6096 m x .6096 m)
Soil Release Technology	Sentry Plus
Installation Method	Vertical Ashlar, Quarter Turn, Monolithic, Brick Ashlar
Indoor Air Quality	Green Label Plus 1098
Foot Traffic Recommendation	Severe
TARR	
NSF 140	Gold (Platinum option available)
PERFORMANCE	
Static	AATCC-134 Under 3.5 KV
Flammability	ASTM E 648 Class 1 (Glue Down)
Smoke Density	ASTM E 662 Less than 450